

MODEL BR FREEBURNER



BURN-RITE'S BR FREEBURNER Range are a simple, low cost effective solution to most waste materials.

The **BR FREEBURNER RANGE** has a number of common features:

Virtually smoke and odour free.

Simple operation with rapid warm up.

Minimal installation



FEATURES

- Burn Rate up to 50kg/hr
- Heat recovery systems available
- Designed for Outdoor Use
- No electrical supply required
- No fuel supply required
- Simple installation
- Steel construction
- 3 versions available

Model No	BR 750 FB
Burn rate/hr. approx.	25kgs
Chamber Volume (m ³)	0.21
External Dimensions, Length (mm)	830
External Dimensions, Width (mm)	800
External Dimensions, Height (mm) excluding flue	1300
Door Opening l x h, (mm)	650 X 470
Flue Diameter. (mm)	225

Model No	BR 500 FB
Burn rate/hr. approx.	10kgs
Chamber Volume (m ³)	0.08
External Dimensions, Length (mm)	500
External Dimensions, Width (mm)	530
External Dimensions, Height (mm) excluding flue	900
Door Opening l x h, (mm)	415 X 320
Flue Diameter. (mm)	150

Model No	BR 1200 FB
Burn rate/hr. approx.	50kgs
Chamber Volume (m ³)	0.63
External Dimensions, Length (mm)	1260
External Dimensions, Width (mm)	1240
External Dimensions, Height (mm) excluding flue	1850
Door Opening l x h, (mm)	980 X 720
Flue Diameter. (mm)	300